



## P ▲ R ▲ D O X

### Wireless volumetric detector

#### NV75MR

#### DETECTION

Detector type	<b>Wireless</b>
Installation height	<b>2.1 m ~ 2.7 m</b>
Angle detection	<b>90°</b>
Detection distance	<b>16 m</b>
Detection method	<b>Infrared</b>
Coverage	<b>16 x 16 m</b>
Pets immunity	<b>Up to 50 cm</b>
Antimasking	<b>Yes</b>
Anti-cloaking technology (activation of alarm after infrared detection AND / OR microwave)	<b>Sí</b>
PIR detection advance at ground level (PIR Creep)	<b>Sí</b>
Detection technology	<b>Volumetric</b>

#### TECHNICAL SPECIFICATIONS

Compatibility	<b>Magellan panels</b>
LED indicators	<b>Yes</b>
Tamper	<b>Yes</b>

#### AMBIENT

Operating temperature	<b>-35 °C ~ 50 °C</b>
Use	<b>Indoor</b>

#### TRASMISSIONE WIRELESS

Frequency	<b>868MHz</b>
-----------	---------------

#### CERTIFICATION

Grade	<b>3</b>
Normative	<b>EN50131</b>
Environmental class	<b>II</b>

#### POWER CONSUMPTION

Battery model	<b>2 x AA</b>
Battery duration	<b>Up to 3 años</b>

#### MATERIAL AND DIMENSIONS

Dimensions	<b>128 x 62 x 54 mm</b>
Net weight	<b>120 g</b>

#### LENS

Lens Type	<b>Fresnel de segunda generación</b>
-----------	--------------------------------------

#### SENSOR

Type of sensor	<b>Dual</b>
----------------	-------------

