



P ▲ R ▲ D O X

Hybrid panel

MG5075

COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
Mobile Network	GPRS / GSM (with PCS module)
3G	Sí

POWER CONSUMPTION

Power mode	DC
Voltage	100V ~ 240V
Amperage	1500mA
Battery support	Optional
Battery model	12V DC 4 ~ 7 ~ 24 Ah

PARTITIONS AND MEMORIES

Partitions	2
User codes	32
Registration events	512

ZONES

Maximum number of zones	32
Wired on-board zones	5

VIA RADIO

Frequency	433MHz / 868MHz
-----------	------------------------

ADDITIONAL FEATURES

Mobile app	INSITE GOLD
------------	--------------------

MATERIAL AND DIMENSIONS

Dimensions	185 x 90 x 30 mm
Net weight	1250 g
Weight with packaging	1440 g

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

AMBIENT

Operating temperature	0 °C ~ 50 °C
Use	Indoor

GENERAL INFORMATION

Type of Central	Hybrid
-----------------	---------------

PROGRAMMABLE OUTPUTS

Maximum of PGMs	16
-----------------	-----------

