



HIKVISION
accessories

IP video intercom for flush mounting

DS-KD3003-E6

INPUTS/OUTPUTS

Wiegand	1
Alarm input	8
RS485	1
Door sensor	2
Exit button	2
Blocking entry	2
Alarm output	2
RJ45	1 x 10 / 100 / 1000

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	70°
Diagonal angle of view	132°
Night vision	Yes, up to 3 m
Video compression	H.264

MATERIAL AND DIMENSIONS

Installation	Embed
Dimensions	357.3 x 124.3 x 55.3 mm
Net weight	1050 g
Weight with packaging	2200 g

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
Screen	Sí
Type of screen	LCD
Screen resolution	320 x 480

OPENING

Call elements	Simple button
Proximity reader	MIFARE cards
Mode	Card / Password / Remote

GENERAL INFORMATION

Technology	IP
------------	----

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	10W
Amperage	1000mA

AMBIENT

Operating temperature	-40 °C ~ 55 °C
Degree of protection	IP65
Use	Indoor-outdoor
Maximum humidity	95%

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX
RAM	512 MB
ROM	4096 MB

AUDIO (VIDEO INTERCOM)

Sound input	Omni-directional microphone
Sound output	Built-in speaker
Audio compression	G.711A / G.711U

CAPACITY

Cards	10000
Linked IP cameras	500

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP / RSTP
------------------	-----------------

