

**HIKVISION**  
intrusion

## Wireless volumetric detector

### DS-PDP15P-EG2-WE

#### DETECTION

|                                                   |                        |
|---------------------------------------------------|------------------------|
| Detector type                                     | <b>Wireless</b>        |
| Installation height                               | <b>2 m ~ 4 m</b>       |
| Angle detection                                   | <b>90°</b>             |
| Detection distance                                | <b>15 m</b>            |
| Detection speed                                   | <b>0,3 m/s ~ 2 m/s</b> |
| Detection zones                                   | <b>84</b>              |
| Pets immunity                                     | <b>Up to 30 Kg</b>     |
| PIR detection advance at ground level (PIR Creep) | <b>Sí</b>              |

#### POWER CONSUMPTION

|                  |                     |
|------------------|---------------------|
| Power mode       | <b>Battery</b>      |
| Built in battery | <b>Yes</b>          |
| Battery model    | <b>CR123A / 3V</b>  |
| Battery duration | <b>Up to 5 años</b> |

#### TECHNICAL SPECIFICATIONS

|                |                         |
|----------------|-------------------------|
| Compatibility  | <b>Hikvision panels</b> |
| LED indicators | <b>Yes</b>              |
| LED colors     | <b>Blue</b>             |
| Tamper         | <b>Yes</b>              |

#### CERTIFICATION

|                     |           |
|---------------------|-----------|
| Grade               | <b>2</b>  |
| Environmental class | <b>II</b> |

#### GENERAL INFORMATION

|       |              |
|-------|--------------|
| Serie | <b>AXPRO</b> |
|-------|--------------|

#### MATERIAL AND DIMENSIONS

|                       |                             |
|-----------------------|-----------------------------|
| Installation          | <b>Wall / ceiling</b>       |
| Dimensions            | <b>103 x 65.5 x 48.5 mm</b> |
| Net weight            | <b>100 g</b>                |
| Weight with packaging | <b>170 g</b>                |

#### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-10 °C ~ 55 °C</b> |
| Use                   | <b>Indoor</b>         |
| Maximum humidity      | <b>90%</b>            |

#### SENSOR

|                                  |            |
|----------------------------------|------------|
| Type of sensor                   | <b>PIR</b> |
| Sensitivity adjustment           | <b>Sí</b>  |
| Digital temperature compensation | <b>Yes</b> |

#### VIA RADIO

|                       |                                         |
|-----------------------|-----------------------------------------|
| Frequency             | <b>868mHz</b>                           |
| Transmission distance | <b>Up to 1600 m (without obstacles)</b> |