



Ip video door station with camera

VTO4201FB-P

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Amperage	2000mA
PoE power	Yes
Type PoE	PoE 802.3af / PoE+ 802.3at
Standby consumption	≤4W
Consumption On	5W
Power output	1 x 12V DC / 600mA

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.9"
Horizontal viewing angle	169°
Diagonal angle of view	177°
Night vision	Si
Day / Night	Imagen en color
Video compression	H.265

INPUTS/OUTPUTS

RS485	1
Door sensor	1
Exit button	1
Blocking entry	1
Alarm output	1
RJ45	1 x 10 / 100

GENERAL INFORMATION

Technology	IP
Type	IP Video Door Station with camera

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Memory slot	SD up to 256Gb
Message recording if no response	Yes (SD card required)

CAPACITY

Cards	3000
-------	-------------

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	100 x 100 x 49.4 mm
Material	Aluminum
Net weight	300 g
Weight with packaging	470 g
Color	Black

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK07
Use	Indoor-outdoor
Maximum humidity	90%

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	Si
Audio compression	G.711A/G.711U/PCM

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	SIP / P2P / IPv4 / UPnP / DNS / RTSP / RTP / TCP / UDP
ONVIF	Yes

